Thank you for requesting an MSDS for this product.

We have reviewed our products, conducted a hazard determination, and prepared MSDSs in compliance with the requirements of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR 1910.1200 and Canada's Workplace Hazardous Materials Information System (WHMIS). Our MSDSs also provide information on any toxic chemical subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA).

If this product, or any component of it, is considered to be hazardous or carcinogenic under the OSHA Hazard Communication Standard or the WHMIS regulations, information is provided in Section 2: COMPOSITION/INFORMATION ON INGREDIENTS or in Section 3: HAZARDS IDENTIFICATION.

MATERIAL SAFETY DATA SHEET

REVISION DATE: 01-21-2004

SUPERSEDES: 01-21-2004

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION

Specialty Construction Brands, Inc. (formerly Foster Products Corporation an H.B. Fuller Company Subsidiary) 315 South Hicks Road Palatine, IL 60067 Phone: 847-358-9500

> Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION PRODUCT IDENTIFIER: PRODUCT NUMBER: PRODUCT NAME: PRODUCT DESCRIPTION:

801791PM CP0090 CHILDERS CP-09 Coating

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS #	PERCENT	OSHA PEL
Crystalline silica	14808-60-7	10 - 30	TWA (Respirable dust) 0.1 MG/M3
Aluminum hydroxide	21645-51-2	10 - 30	TWA (as Al) Soluble 2 MG/M3
Titanium dioxide	13463-67-7	1 - 5	TWA (Total dust) 10 MG/M3
Cellulose	9004-34-6	1 - 5	TWA (Respirable dust) 5 MG/M3 TWA (Total dust) 15 MG/M3
Vinyl acetate	108-05-4	0.1 - 1	TWA 10 ppm STEL 20 ppm

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Cancer hazard.

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY EYE: Can cause minor irritation, tearing and reddening. SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Overexposure to crystalline silica may cause silicosis.

INGESTION: Ingestion is not an anticipated route of exposure. No hazard in normal industrial use.

LONG-TERM (CHRONIC) HEALTH EFFECTS TARGET ORGAN(S): Lungs

REGULATED CARCINOGEN STATUS: Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica Vinyl acetate

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT:	Non flammable
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	There is a possibility of pressure buildup in closed containers
	when heated. Water spray may be used to cool the containers.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-
	contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	No adverse health effects expected from the clean-up of spilled material.	
	Follow personal protective equipment recommendations found in Section 8	
	of this MSDS.	
CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers	
	for disposal. Keep spilled product out of sewers, watersheds, or water	
	systems.	
	Avoid creating dusts. Cover material with absorbent and moisten and collect	
	for disposal.	

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: No special handling instructions due to toxicity. Avoid breathing material.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION:	Wear safety glasses when handling this product.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves.
GLOVES:	Not normally required. Use nitrile gloves if conditions warrant.
RESPIRATORY PROTECTION:	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).
VENTILATION:	Use local exhaust ventilation or other engineering controls to minimize exposures.

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL	
Crystalline silica	TWA (Respirable dust) 0.05 MG/M3	Not established	
Aluminum hydroxide	TWA (as Al) Soluble 2 MG/M3	Not established	
Titanium dioxide	TWA (Total dust) 10 MG/M3	Not established	
Cellulose	TWA (Total dust) 10 MG/M3	Not established	
Vinyl acetate	TWA 10 ppm STEL 15 ppm	Not established	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
COLOR:	White
ODOR:	Sweet
ODOR THRESHOLD:	Not established
WEIGHT PER GALLON (lbs.):	11.00
SPECIFIC GRAVITY:	1.32
SOLIDS (% by weight):	66.0
pH: BOILING POINT (deg. C): FREEZING/MELTING POINT (deg. C): VAPOR PRESSURE (mm Hg): VAPOR DENSITY: EVAPORATION RATE: OCTANOL/WATER COEFFICIENT:	Not established Not established Not established Not established Not established Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY:Stable under normal conditions.CHEMICAL INCOMPATIBILITY:Not establishedHAZARDOUS POLYMERIZATION:Will not occur.HAZARDOUS DECOMPOSITION PRODUCTS:Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50	
Crystalline silica	Not established	
Aluminum hydroxide	Not established	
Titanium dioxide	Not established	
Cellulose	Oral LD50 Rat > 5 g/kg	
	Inhalation LC50 Rat > 5800 mg/cu m/4H	
	Dermal LD50 Rabbit > 2 g/kg	
Vinyl acetate	Oral LD50 Rat = 2920 mg/kg	
-	Inhalation LC50 Rat =11400 ml/cu m	
	Dermal LD50 Rabbit = 2335 mg/kg	

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information. DOT: NOT REGULATED IATA: NOT REGULATED

SECTION 15: REGULATORY INFORMATION

 INVENTORY STATUS

 U.S. EPA TSCA:
 This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

 CANADIAN CEPA DSL:
 This product is in compliance with the Canadian Domestic Substance List requirements.

 If you need more information about the inventory status of this product call 651-236-5858.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Vinyl acetate	108-05-4	0.1 - 1
		,

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A

STATE REPORTING This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Specialty Construction Brands, Inc. from its suppliers, and because

801791PM 01-21-2004

MATERIAL SAFETY DATA SHEET

Specialty Construction Brands, Inc. has no control over the conditions of handling and use, Specialty Construction Brands, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Specialty Construction Brands, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Specialty Construction Brands, Inc. products to comply with all applicable federal, state and local laws and regulations.